



FEATURE

- All metal welded package
- Wide frequency range from 32 KHz upto 210 MHz
- CMOS IC circuit construction built in with Tristate function
- HCMOS / TTL compatible in general application
- RoHS Compliant Standard

Table 1

Codes	Stability Codes	D	E	F	G	M	K
		±10 PPM	±15 PPM	±20 PPM	±25 PPM	±50 PPM	±100 PPM
A	0 to +50° C						
B	0 to +60° C						
F	0 to +70° C						
D	-10 to +60° C						
E	-10 to +70° C						
C	-20 to +70° C						
G	-30 to +80° C						
H	-30 to +85° C						
I	-40 to +85° C						
J	-40 to +90° C						
K	-55 to +105° C						
L	-55 to +125° C						

Denotes Available Denotes not Available

Table 2

Supply Voltage	5V		3.3V
Series	CXO-100	CXO-600	CXO-225
	CXO-200	CXO-800	CXO-825

MECHANICAL SPECIFICATIONS

	Full Size	Half Size
Top View		
Front View		
Bottom View		

Note: Sharp edge indicates Pin 1. ▲ All dimensions are in mm.

Pin Configuration for Full Size-DIL 14

- 1: No connection
- E/D control (optional)
- 7: Ground
- 8: Output
- 14: DC Input

Pin Configuration for Half Size-DIL8

- 1: No connection
- E/D control (optional)
- 4: Ground
- 5: Output
- 8: DC Input


Parameters	Variant	
	HCMOS	TTL
Series: CXO-100 (Full size-DIL14) CXO-200 & CXO-225 (Full size-DIL14) CXO-600 (Half size-DIL8) CXO-800 & CXO-825 (Half size-DIL8)	■	■
Frequency Range: 32 KHz – 160 MHz (CXO-100 & CXO-600) 32 KHz – 160 MHz (CXO-200 & CXO-800) 32 KHz – 210 MHz (CXO-225 & CXO-825)	■	■
Output Drive: 50 pF max. 1 to 10 TTL gates	■	■
Logic Levels: '0' = 0.4V max. '1' = 2.4 Vmin. '0' = 10% of Vcc max. '1' = 90% of Vcc min.	■	■
Rise / Fall time: 10 ns max. (Between Logic 0 & Logic 1 Level)	■	■
Start up time: 10 ms max	■	■
Waveform Symmetry: 40 to 60 % @ 1.4 V DC 40 to 60 % @ ½ Vcc	■	■
Output Waveform: Square Wave	■	■
Frequency Stability: (Table 1)	□	□
Temperature Range: (Table 1)	□	□
Supply Voltage (Vcc): (Table 2) +5.0V DC (±10%) +3.3V DC (±10%)	■	■
Supply Current: For 5 Volts 30 mA max (32 KHz – 24 MHz) 40 mA max (24 MHz – 50 MHz) 50 mA max (50 MHz – 80 MHz) 80 mA max (80 MHz – 160 MHz)	■	■
Supply Current: For 3.3 Volts 15 mA max (32 KHz – 24 MHz) 20 mA max (24 MHz – 50 MHz) 25 mA max (50 MHz – 80 MHz) 40 mA max (80 MHz – 120 MHz) 50 mA max (120 MHz – 210 MHz)	■	■
Tristate (Optional) (E/D Option): Out put enable when Pin 1 is 2.0 V DC min. (or) Open /output disable when Pin 1 is 0.8V DC max. (or) Ground	■	■
Ageing: ± 5 ppm per year max.	■	■
Storage Temperature Range: -55 to +125° C	■	■

■ Standard, □ Optional – please specify required code(s) when ordering.

Ordering Information

Example

CXO 200 B G N 010M000000



Specifications subject to change without notice
Revision No. 12b of May 2008

ANDHRA ELECTRONICS LIMITED

34 & 35, IDA, Kakinada, AP – 533 005,
INDIA.
URL: www.andhraelec.com

Phone: +91-884-2342203
Fax: +91-884-2341145
E-mail: info@andhraelec.com