



Features:

- Wide Frequency Range
- Design Available in 2-8 Sections
- Fast Prototype and Delivery Available

MECHANICAL DIMENSIONS	
Top view	
Front View	
Bottom View	
Side View	

ELECTRICAL SPECIFICATIONS	
PARAMETER	SPECIFICATIONS
Center frequency	240MHz
1dB Band width	<6MHz
Rejection	DC-180MHz,>60dBc >300MHz,>60dBc.
Insertion loss	<2dB
Return loss	@Fc,>10dB
Impedance	50 ohms
Power handling	1watt
Package	SMD
Operating temperature	-40°C to +85°C
Storage temperature	-40°C to +85°C
Dimensions	44.53X14.92X11.00 mm

Table

Insertion Loss (dB)	Return Loss(dB)	OTR (°C)	No. of Poles
1 → ≤1	A → 10 Min	B → 0 to +60	A → 3
2 → <2	B → >10	C → -20 to+70	B → 4
3 → <3	C → >12	D → -10 to +60	C → 5
4 → <4	D → >14	G → -30 to +80	D → 6
5 → <5	E → >15	I → -40 to +85	E → 7
6 → <6		K → -55 to +105	F → 8
7 → <7		L → -55 to +125	G → 9
8 → <8			H → 10
9 → >8			I → 11
			J → 12
0 - Not Assign	N - Not Assign	N - Not Assign	K → 13

Ordering Information

AE/LC/BPF

C1	2	B	I	A	240/6M	X
Series	Insertion loss	Return loss	OTR	No. of poles	Freq/BW	Optional